

## 100m<sup>3</sup> Double-Wall Portable Water Tanks

**[Inventory ID #1400623]**



100m<sup>3</sup> Double-Wall Portable Water Tanks

Quantity: 3 Units

- Inner Tank Capacity: 100m<sup>3</sup> (26,417.2 US Gallons)
  - Dual Compartments: 40m<sup>3</sup>/60m<sup>3</sup>
- Total Containment Volume: 139m<sup>3</sup> (36,720 US Gallons)
- Overflow: 40m<sup>3</sup> (10566.9 US Gallons) Overflow Capacity
- Material: Steel
- Condition: New/Unused
- Comes With:
  - Diesel Powered Water Heating System
  - 500 Gallon Diesel Fuel Tank
  - Pump to Circulate the Water
  
- Sealed Double Wall Construction
- No Through-The-Wall Penetration
- All Fill and Suction Lines Pass Through Roof
- 3" Fill and Recirculation Lines
- 4" Suction Lines Reduced to 3" Connection Point
- All Lines Come with Shutoff Valves and Cam Lock Fittings
- Sight Glass for Containment Tank Inspection
- Spill Containment with Bar Grate Under Roof
- 4" Suction for Containment Tank Drain in Case of Overflow
- Roof Access Ladder with Fall Restraint
- Full Length Fall Restraint Cable on Roof
- 24" Hinged Manway on Roof
  
- Tank Monitoring System - Optional Add-on, Call For Pricing

- Siemens Controls and Interface
  - Siemens Radar Level Sensor
  - Plug-and-Play (Up to 6 Tanks)
  - Hot Swappable Analogue Inputs
  - Visual Tank Level Status on a 7" Colour Display
  - Audible (Horn) and Visual (Strobe) High and Low Alarm Indication
- 
- Dimensions:
    - Length: 50' (15.24m)
    - Width: 10' 6" (3.2m)
    - Height: 11' 9" (3.58m)
    - Weight: 44,000 Lbs. (19,958 kg)
- 
- Applications:
    - Mobile Fire Water Storage System for Remote Locations
    - Invert Storage and Management
    - Volatile Fluids
    - Manage Drilling Fluids
    - Fluid Storage and Staging During Plant Shutdowns
    - Fluid and Spill Containment
    - Base Oil
    - Environment Spill Containment
    - Containment in Emergency Response Situations
- 
- Location: Canada

View More [Steel Tanks](#)