

Consep H&S 1365 Linear Sampler Package

[Inventory ID #1611522]



Consep H&S 1365 Linear Sampler Package

Currently Available as Part of 24000 TPD Package ONLY

See Listing Here - [1000 TPH / 24000 TPD Gold Plant Equipment with Gravity Concentration](#)

- (2) Primary Sampler:
 - Make: Heath & Sherwood (H&S) - Consep
 - Model: 1365 Linear
 - Type: Auto Sampler
 - Condition: New Surplus Condition
 - Feed Type: Continuous, Horizontal
 - Inlet Size: 3,200mm Wide x 600mm High
 - Cutter: P800 Pelican Cutter
 - Cutter Travel: 4,000mm
 - Cutter Speed: 450mm/s
 - Cutter Aperture: 40mm
 - Construction: 304 Stainless Steel
 - Mild Steel Cutter Hanger
 - Cutter Blades: Adjustable - 316 Stainless Steel
 - Proximity Sensors
 - Lubrication System: Automatic
 - Drive: Electric Motor
 - Power Output: 2.2kW
 - Voltage: 400 Volts
 - Frequency: 50Hz
 - Phase: 3-Phase
 - Integrated Cutter Enclosure
 - Liners: 6mm Remaline 40 Rubber
- (2) Swirl Tank: ST100

- Size: 100 Liter
- (2) Secondary Sampler:
 - Make: Heath & Sherwood (H&S) - Consep
 - Model: 4810 Rotary Vezin
 - Type: Auto Sampler
 - Style: Dual Cutter
 - Condition: New Surplus Condition
 - Feed Type: Vertical Pipe/Gravity
 - Inlet Size: 80mm NB
 - Radial Cutters: (2)
 - Cutter Aperture @ Midpoint: 48mm
 - Construction: 304 Stainless Steel
 - Cutter Blades: Adjustable - 316 Stainless Steel
 - Proximity Sensors
 - Spray Nozzle
 - Lubrication System: Automatic
 - Drive: Electric Motor
 - Power Output: 0.37kW
 - Voltage: 400 Volts
 - Frequency: 50Hz
 - Phase: 3-Phase
 - Cutter Enclosure: Mild Steel
 - Liners: Remaline 40 Rubber
- (2) Swirl Tank: ST30
 - Size: 30 Liter
- (2) Tertiary Sampler:
 - Make: Heath & Sherwood (H&S) - Consep
 - Model: 4810 Rotary Vezin
 - Type: Auto Sampler
 - Style: Dual Cutter
 - Condition: New Surplus Condition
 - Feed Type: Vertical Pipe/Gravity
 - Inlet Size: 65mm NB
 - Radial Cutters: (2)
 - Cutter Aperture @ Midpoint: 48mm
 - Construction: 304 Stainless Steel
 - Cutter Blades: Adjustable - 316 Stainless Steel
 - Proximity Sensors
 - Spray Nozzle
 - Lubrication System: Automatic
 - Drive: Electric Motor
 - Power Output: 0.37kW
 - Voltage: 400 Volts
 - Frequency: 50Hz
 - Phase: 3-Phase

- Cutter Enclosure: Mild Steel
 - Liners: Remaline 40 Rubber
- (2) Sample Dewatering Module: Double-Body Vacuum Filter
 - Size: 600mm Dia.
 - Diaphragm Vacuum Pump: Pneumatic
 - Vacuum Piping
 - Valves
- (2) Control System: Timer Based
 - For Primary, Secondary and Tertiary Samplers

[See Complete Plant Listing Here to View Additional Available Equipment](#)

Read More About This Liquidation [Here](#)

View More [Laboratory Equipment](#)