

## Getman A64 SL Scissor Lift

**[Inventory ID #190776]**



- Offers a maximum platform height of 4.2 m. (14 Ft.) with a capacity of up to 2,720 kg (6,000 lb).
- Comes equipped with a telescoping ladder that allows for easy access and egress from the platform without having to lower the platform.
- Available fold-down wings or sliding platform features provide added flexibility to perform required functions without repositioning the machine.
- Protects miner safety through purpose-built design, including a fully stabilized non-skid platform with leveling capability and fall arrest anchor points located throughout the basket for quick and easy tie off.
- The lifting structure is compliant with all relevant ANSI, CSA and AS standards.
- Engine:
  - Tier III approved engine - 4-cylinder.
    - Mercedes Benz OM904LA, 129 kW (173 hp) @ 2200 rpm.
    - Cummins QSB4.5, 127 kW (170 hp) @ 2200 rpm.
  - Liquid-cooled, turbocharged.
  - 113 L (30 gal) fuel tank with self-closing cap.
- Exhaust System:
  - Catalytic exhaust conditioner and silencer.
- Transmission:
  - Dana Clark 32000 powershift transmission.
  - Three speeds forward and reverse.
  - 4-wheel drive.

- Axles:
  - Planetary drive axles.
    - Heavy-duty Carraro 28.43 axle package.
    - Enhanced capacity Carraro 28.60 axle package.
- Tires:
  - Mine service tires.
    - 10.00x20-16pr.
    - 12.00x20-28pr.
- Brake System:
  - Fully hydraulic wet disc service brakes on each axle.
  - Spring applied, hydraulic pressure release wet disc secondary brake.
  - Automatic secondary brake application upon loss of brake accumulator pressure, transmission pressure or electrical power.
- Steering:
  - Orbitrol controlled articulated frame steering.
  - Heavy-duty, self-aligning bearings inside replaceable inserts.
  - Two double-acting steer cylinders with replaceable bushings in cylinder and frame ears.
  - 40° articulation each direction.
- Hydraulic System:
  - Hot side/cold side engine layout.
  - Hydraulic hoses routed to cold side of engine.
  - Open center hydraulic circuits with gear hydraulic pump.
  - Diagnostic test ports with quick couple fittings for: each axle, service brake application pressure, and hydraulic pumps.
  - 10-micron return filter.
  - 151 L (40 gal) hydraulic reservoir.
- Operator Compartment:
  - Three-point contact for entry and exit.
  - ROPS/FOPS certified compartment (SAE J1040C, CSA B-352, ISO 3471).
  - Open canopy.
  - Enclosed cabin with heater and air conditioner.
  - Operator and passenger seating.
  - Mechanical suspension operator seat.
  - Retractable lap seat belts.
- Other General Equipment:
  - Variable audio backup alarm (87-112dBA).
  - 2.3 kg (5 lb) fire extinguisher.
  - Wheel chocks.
  - Four nozzle Ansul fire suppression system tied to engine shutdown (LTA-101-30).
- Location: Eastern USA

View more [Scissor Lifts](#)