

IMEFY 2200 kVA Oil Filled Transformer

[Inventory ID #196772]



- General Data:
 - Power Rating: 2200 KVA.
 - Primary Voltage: 33 kV.
 - Secondary Voltage: 420 V.
 - Tappings: $\pm 2,5 \pm 5$ %.
 - Vector Group: Dyn11.
 - Frequency: 50 Hz.
 - Cooling: ONAN.
 - Ambient T^a /Av. Winding T^a rise / Oil T^a rise 40°C / 65 K / 60 K.
 - Insulation Levels HV (Vmax / LI / AC) 36 / 170 / 70 KV.
 - Insulation Levels LV (Vmax / LI / AC) 1,1 / 20 / 10 KV.
 - Material: HV/LV Aluminum / Aluminum.
 - Standards: IEC 60076-1.
 - (UE) N°548/2014.
- Electrical Data
 - No-load losses: 1800 W.
 - Load losses to 75°C: 21600 W.
 - Short-circuit voltage to 75°C 6 %.
 - Sound power Lw(A): 61 dB(A).
- Approximate Dimensions & Weight
 - Length 2490 mm.
 - Width 1560 mm.
 - High 2450 mm.
 - Total weight 6650 Kg.

View more [Liquid Filled Transformers](#)