

P.O. Box 176, Savona, BC, Canada V0K 2J0 Phone: (250) 373-2424 Fax: (250) 373-2323 Website: savonaequipment.com Email: sales@savonaequipment.com Located just 20 minutes west of Kamloops, BC

John Deere 770 Grader [Inventory ID #1337855]



John Deere 770 Grader

- Make: John Deere
- Model: 770A
- Year: 1977
- Condition: Used, Reported in Good Condition
- General Model Specifications:
 - Engine
 - Number Of Cylinders: 6
 - Engine Make: John Deere
 - Engine Model: 6-466A
 - Power Measured @ 2200rpm
 - Torque Measured @ 1300rpm
 - Max Power: 150HP
 - Net Power Gears 7-8: 150HP
 - Net Torque Gears 7-8: 465 ft-lbs
 - Displacement: 466in³
 - Aspiration: Turbocharged with Intercooler
 - Operational:
 - Std Operation Weight Front Axle: 8,548 lbs.
 - Std Operation Weight Rear Axle: 21,712 lbs.
 - Std Operation Weight Total: 30,260 lbs.
 - Max Operation Weight Front Axle: 9,091 lbs.
 - Max Operation Weight Rear Axle: 24,758 lbs.



- Max Operation Weight Total: 33,849 lbs.
- Hydraulic System Fluid Capacity: 31 Gal
- Oil System Fluid Capacity: 5 Gal
- Fuel Capacity: 70 Gal
- Cooling System Fluid Capacity: 7.1 Gal
- Circle Gearbox Fluid Capacity: 1.1 Gal
- Tandem Case Fluid Capacity (Each): 5 Gal
- Tire Size: 14.00-25
- Operating Voltage: 24V
- Alternator Supplied Amperage: 42 Amps
- Steering:
 - Articulation Angle: 25°
 - Turning Radius: 22ft

• Transmission:

- Transmission Type: Power Shift
- Number Of Gears Forward: 8
- Number Of Gears Reverse: 4
- Max Speed Forward: 25.1 mph
- Max Speed Reverse: 8.6mph

• Front Axle:

- Wheel Lean: 20°
- Oscillation Total: 30°
- Ground Clearance: 1.9ft
- Moldboard:
 - Moldboard Width: 12ft
 - Moldboard Height: 24in
 - Moldboard Thickness: 0.9in
 - Side Shift Left: 26.9in
 - Side Shift Right: 26.9in
- Hydraulic System:
 - Pump Type: Closed Center Variable Displacement
 - Pump Flow: 36 Gal/Min
- Circle:



- Diameter: 59.1in
- Rotation: 360°
- Shift Left: 33.6in
- Shift Right: 32.1in
- Max Reach Outside Tires Left: 89.8in
- Max Reach Outside Tires Right: 88.6in
- Max Lift Above Ground: 17.1in
- Blade Tip Angle Front: 44°
- Blade Tip Angle Rear: 10°
- Location: Western Canada

View More Motor Graders