

## [RDH Cretemaster 600R Concrete Remixer](#)

**[Inventory ID #1296203]**



RDH Cretemaster 600R Concrete Remixer

### **Quantity: 2 Units Available**

- Make: RDH/Maxon
- Model: Cretemaster 600R/4.50M
- Serial(s): 259, 260
- Year: 2014
- Drive: 4WD
- Articulated Heavy-Duty Frame
- Proven to Withstand Impacts and Stresses of Mining Application
  
- General Model Specifications:
  - Concrete Drum:
    - Maximum Transportation Capacity: 4.5m<sup>3</sup> (5.9yds<sup>3</sup>)
    - Drum Volume: 5.2m<sup>3</sup> (6.8yds<sup>3</sup>)
    - Hydraulically Operated Mixing and Loading
    - Adjustable Rotation Speed in Both Directions: 0-13 RPM
    - Abrasive Resistant Steel Drum
    - Two Round Filling Hatches
    - Aluminum Rear Hatch
    - 2 Heavy-Duty Support Bearings
    - 2 Heavy-Duty Roller Bearings



- Engine:
  - Make: Cat® C6.6 ACERT Diesel Engine Tier 3
  - Power Rating: 212HP (158kW) @2200 RPM
  - Compression Ratio: 16.5:1
  - Displacement: 6.6 L (402.8 in<sup>3</sup>)
  - Exhaust: Catalytic Purifier with Silencer
  - Fuel Tank Volume: 227 L
  
- Transmission:
  - Make: Dana Powershift, 32000-Series
  - Speeds: 4 Speeds Forward and Reverse
  - Drive: 4 Wheel Drive
  
- Axles:
  - Make: Dana 113
  - Type: Planetary
  - Oscillation (Rear Axle): +7°
  
- Brakes:
  - Service: Wet Disc (Integrated), Internal SAHR
  - Emergency & Parking: SAHR
  
- Steering:
  - Type: Hydraulic, Articulated
  - Steering Angle: +38°
  
- Hydraulics
  - Drum: 170 bar, 190 L/min/2200 rpm
  - Steering: 152 bar, 76 L/min/2200 rpm
  - Hydraulic Oil Tank Volume: 227 L
  
- Electrical System
  - Voltage: 24 V
  - Battery: 2 x 12 VDC
  - Trimming/Working LED Lights: 4 Front / 4 Rear
  - Brake Lights: 2 Rear
  - Horn & Reverse Alarm



- Miscellaneous
  - Central Grease Point – Manual
  - Standard Gauges and Instrumentation
  - ANSUL Fire Suppression System - Manual
  - Copy of Parts/Operator/Service Manuals
  - Passenger Seating
  - Suspension Seating (Operator/Passenger)
  - ROPS/FOPS Certified Canopy
  - Hydraulic Driven Air Compressor
  - Articulated Heavy-Duty Frame
  
- Overall Dimensions:
  - Length: 317in
  - Width: 93in
  - Height: 108in
  - Weight: 35,186 Lbs.
  
- [View Spec Sheet Below](#)
  
- Location: Western Canada

View More [Underground Service Vehicles](#)