

Sandvik Toro 40 Underground Haul Truck

[Inventory ID #252861]



- **Truck Hours: 9,800**
- **Year: 2008**
- **Dimensions:**
 - Total Length: 10,217 mm (402 in.).
 - Total Width: 2,990 mm (118 in.).
 - Height: 2,670 mm (105 in.).
 - Max. Height of the box: 2760 mm (109 in.).
- **Weights:**
 - Operating Weight: 30,700 kg (67,700 lb).
 - Total loaded weight 70,700 kg (155,900 lb).
 - Axle weights without load:
 - front axle 22,200 kg (49,000 lb).
 - rear axle 8,500 kg (18,700 lb).
 - Axle weights with load:
 - front axle 33,400 kg (73,600 lb).
 - rear axle 37,300 kg (82,200 lb).
- **Capacities:**
 - Payload capacity: 40,000 kg (88,125 lb).
 - Box std.: 18.0 m³ (24yd³).
- **Dump box movements:**
 - Discharging time: 13 sec.
 - Dumping angle: 62°.
- **Frame:**
 - Rear and front frame: Welded steel construction.
 - Material: Raex 384 (St 52-3).
 - Central hinge: Box constructed, adjustable lower bearing.
 - Firewall.
- **Engine:** Detroit S-60 DDEC IV:

- Diesel Engine.
- Output: 354 kW / 2100 r/min (475 HP).
- Torque: 2102 Nm / 1350 rpm.
- Number of cylinders: in line 6.
- Cooling system: water cooled.
- Combustion principle:
 - Direct injected.
 - Turbo + inter cooler.
 - 4 stroke.
- Air Filtering: Donaldson.
- Exhaust System:
 - HTI covered exhaust manifold & Turbo
 - Double wall exhaust pipe
 - Catalytic purifier & muffle
- Fuel Tank Capacity: 550 l (145 gal.)
- Dana SOH 8821 **Gearbox**:
 - Power shift transmission with electric remote shifting.
 - 8 forward gears.
 - 2 reverse gears.
- Dana axles.
- **Brakes**: Service and emergency brake are fully hydraulic.
 - Dana liquid cooled LCB.
- Ansul fire suppression system.
- Rear Backup Camera.
- Automatic Hydraulic Lubrication System.
- Box: conventional.
- ROPS/FOPS canopy meets CSA B352 standards.
- Overall Condition: Good, used.
- Location: Savona British Columbia

View more [Underground Trucks](#)

Watch YouTube Video: <https://www.youtube.com/watch?v=s1YKKVJWMw8>