

Sandvik Toro 40D Underground Haul Truck

[Inventory ID #1124346]



Sandvik Toro 40D Underground Haul Truck

- Make: Sandvik
- Model: Toro 40D
- Year: 1996
- Condition: Good
- Box Size: 18m³ (24yd³)
- Payload: 40,000 kg (88,125 lbs)

- Engine: Detroit S-60 DDEC IV Diesel (475HP, 1550 Ft-Lbs @1350 RPM)
- Torque Converter: Dana SOH, CL 8672 One stage, Offset 1.118:1
- Transmission: Dana SOH, 8821
 - Power-Shift Transmission With Electric Remote Shifting System
 - 8 Gears Forward and 2 Gears Reverse
- Axles:
 - Front Axle: Dana SOH, 21D 3847, Oscillation ± 9°.
 - Rear Axle: Dana SOH, 21D 3847, Fixed
- Brakes: Fully Hydraulic Dana SOH Liquid Cooled Brakes (LCB)
- Tires: 26.5R25, Bridgestone VALS E4 - Very Good Rubber
- Canopy: ROPS Open Cab

- Overall Dimensions
 - Length: 10,217 mm (402")
 - Width: 2,990 mm (118")
 - Height: 2,760 mm (109")
 - Weight: 30,700 kg (67,700 lbs)

- Additional Notes:
 - Dump Box Movements
 - Discharging Time: 13 Seconds
 - Dumping Angle: 62°
 - Frame
 - Rear and Front Frame: Welded Steel Construction
 - Material: Raex 384 (St 52-3)
 - Central Hinge: Box Constructed, Adjustable Lower Bearing
 - Steering System
 - Full Hydraulic, Center Articulated, Power Steering with 2 Double Acting Cylinders
 - Steering Pump: David Brown
 - Steering Cylinders: Tamrock
 - Steering Valves: Danfoss
 - Turning Angle: $\pm 42.5^\circ$
 - Turning Radius
 - Inner 4,944 mm (195")
 - Outer 9,000 mm (354")
 - Box Hydraulics
 - Full Hydraulic Servo Controlled System, Equipped with Heavy-Duty Gear Pump
 - Cylinders for Dump Box Valves: Tamrock
 - Valves for Dump Box: David Brown
 - Pump for Dump Box Hydraulics: Commercial
 - Pump for Servo Circuit: David Brown
 - Fittings: ORFS
 - Electrical Equipment
 - Alternator 24Volt, 140Amp, Bosch
 - Batteries: 2 pcs, 12Volt, 160Ah
 - Starter: 24Volt
 - Fuel Tank Capacity: 550 Liters (145 gal.)
 - Centralized Manual Lubrication
- Location: Canada

View More [Underground Trucks](#)