

ScrewSucker 125H Diesel Pump [Inventory ID #207223]



- **Pump Capacity:**
 - Large pump capacity combined with a low engine power rating.
 - Capable of pumping unscreened raw sewage water and viscous liquids.
- **Vacuum system:**
 - Can handle large quantities of air.
 - Up to 60 cfm, standard is 15 cfm.
- **Discharge and Suction connections Flange:** 6" 125 LB. ANSI.
- **Capacity (maximum @ 1800 RPM):** 1900 GPM.
- **Head (maximum @ 1800 RPM):** 136 Feet.
- **Engine Type and Make:** Caterpillar C2.2 Water Cooled.
- **Engine Power Rating:** 23 HP @ 1500 RPM. 29 HP @ 1800 RPM.
- **Pump Type and Manufacture:** E 125-H Hidrostal Screw Centrifugal.



- **Required Pump Power:** 14.7 HP @ 1500 RPM and 28 HP @ 1800 RPM.
- **Engine Starting System:** 12 volt DC manual and automatic level switching.
- **Capacity Diesel Tank:** 66 gallons sufficient for 72 hours continuous running at maximum load.
- **Acoustic Canopy:** Noise emissions reduced to 60 dB(A) at 23 feet distance.
- **Weight:** Approximately 3880 lbs.
- **Canopy Features:**
 - The canopy doors can be locked. The canopy serves as a containment vessel to prevent leakage from the unit. The vessel also has a built in oil/water separator. A hand pump is built in to assist in pumping out diesel engine sump and containment fluids. The entire canopy is constructed from galvanized steel sheeting.
- **Near new condition:**
 - Hours: 52, 54, and 125.

View more [Portable Pumps](#)