

P.O. Box 176, Savona, BC, Canada V0K 2J0 Phone: (250) 373-2424 Fax: (250) 373-2323

Website: savonaequipment.com Email: sales@savonaequipment.com

Located just 20 minutes west of Kamloops, BC

## Tracked Hydracore 2000 Diamond Core Drill

[Inventory ID #1268503]



## Tracked Hydracore 2000 Diamond Core Drill

Make: HydracoreModel: 2000

• Condition: Used, Reported in Good Condition

• Mounted on Tracked Carrier

Marooka MTS 700

New Rubber Tracks

- New Style Hydracore Head
- Stringer has been Revamped
- Engine Had Cylinder Replaced
  - Engine has been Maintained Regularly
- Spare Deutz Engine
  - Spare Engine has been Maintained Regularly
- Injectors have been Redone
- Pumps have Been Rebuilt
- Spare Hydraulic Pump
- Fully Enclosed Shack with Pony Walls for Cold Climates
- Hydraulic Leveling Jacks
- General Model Specifications:
  - Depth Capacity:

B Size: 5,700 feet (1,750m)
N Size: 4,250 feet (1,300m)
H Size: 2,700 feet (825m)

Drill Head



P.O. Box 176, Savona, BC, Canada V0K 2J0 Phone: (250) 373-2424 Fax: (250) 373-2323

Website: savonaequipment.com Email: sales@savonaequipment.com

Located just 20 minutes west of Kamloops, BC

- H Size Hydraulic Chuck
- Belt Drive with 2.77:1 Ratio
  - Torque
    - Maximum: 1,254 ft-lbs. @522 RPMMinimum: 428 ft-lbs. @1,500 RPM
    - More Torque is Available in Reverse for Rod Breaking, (1,790 ft-lbs.) Reverse Pressure is set at 5,000 PSI While Max Pressure Forward is 3,500 PSI
- Hydraulic Chuck (Hydracore Link Chuck)
  - Operation: Spring Closed, Hydraulic Opened
  - Axial Thrust: 30,000 lbs.
  - Capacity: B to HNo. of Jaws: 3
  - Maximum Rod Size: 3-1/2 inches
- Foot Clamp
  - Operation: Accumulator Closed, Hydraulic Opened
  - Axial Thrust: 25,000 lbs.
  - Capacity: B to PNo. of Jaws: 2
  - Maximum Rod Size: 4-1/2 inches
- Drill Slide and Feed Cylinder
  - Maximum Pull: 24,000 lbs.Maximum Thrust: 16,000 lbs.
  - Stroke: 70 inchesLength: 122 inches
- Location: Western Canada

View More **Diamond Core Drills**